



# QX500

The QX500 IP PBX designed for offices with as many as 500 users. The QX500 can support up to 500 IP devices and 80 concurrent calls. SIP trunking allows for the QX500 to connect directly to an ITSP with no additional equipment. The QX500 includes a firewall and SIP Intrusion Detection for optimal security. E1, T1, FXO, ISDN BRI and FXS ports can easily be provided using the Epygi QX Gateways.



IP phones	100
Additional IP phones with keys	400
Total phones	500
Concurrent calls	80
Ethernet LAN port (10/100/1000)	1
Ethernet WAN port (10/100/1000)	1
Audio In port	1
Audio Out port	1
SD slot	1

## Interconnection with QX Gateways

GATEWAYS	Recommended Number (max)
QXFXO4	24
QXISDN4	12
QXE1T1	2
QXFXS24	16

# FEATURES

## Telephony

### PBX Features

- Auto Attendant with Customizable Scenarios
- Call blocking, forwarding, hold, transfer, Call Relay and call waiting
- Caller ID detection and hiding caller ID
- Voicemail system
- Voicemail notification via SMS/email
- Caller ID-based voicemail profile
- Call park, call pickup, paging, intercom
- Distinctive ringing
- Speed dial
- Many Extension Ringing
- Receptionist
- Call hunting
- Automated call back from Auto Attendant
- Hold music
- Call history
- Do Not Disturb
- Global speed dial
- Find Me/Follow Me
- Unified Messaging
- Three-way conferencing
- G3 fax support: T.38 and clear channel fax
- Universal Extension Recordings
- Busy auto redial
- Directory assistance
- Phone Book
- Authorized Phones
- Dial plans (call routing), time of day routing
- Scheduling, Day/Night Switching
- Alarm
- Dial & Announce (D&A)
- Class of Service
- Call queue
- Redundancy\*
- Automatic Call Distribution (ACD)\*
- Epygi ACD Console (EAC)\*
- Epygi Hotel Console (EHC)\*
- Call Recording (48 ports)\*
- Barge-In\*
- Conference Server\*
  - Audio (48 ports)/Video (24 ports)
- iQall Mobile Toggling\*

### PC-Based Applications

- Desktop Communication Console (DCC)\*
- Auto Dialer\*

\*Requires a software license key

### Voice and Video Features

- Voice Coding:
  - G.711, G.726 (16, 24, 32, 40 Kbps), G.729A, iLBC (13,33 kbit/s, 15,2 kbit/s); VAD, CNG, G.168 echo cancellation
  - G.722 and G.722.1 pass-through point-to-point HD call
- Video Coding:
  - H.263, H.263+ and H.264 pass-through point-to-point video call
- VoIP Encryption:
  - SRTP
- VoIP Signaling:
  - SIP v2, SIP/TLS
  - DTMF:
  - In band & out of band signaling support

### VoIP Data and Signaling Protocols

- ITU-T G.711, G.726, G.729 Annex A, G.168-2000, 2002, Q.23, Q.24;
- IETF RFC 3951- iLBC;
- Telcordia (Bellcore) GR.506, GR.181; ETS\_300 659\_1,2,3;
- SIP, SIP/TLS (RFCs: 2246, 3261, 3263, 3265, 3311, 3323, 3428, 3515, 3578,

- 3581, 3842, 3856, 3863, 3891, 3892, 4028, 4235)
- SDP (RFC: 2327, 4568)
- RTP/SRTP (RFCs: 1889, 1890, 3389, 3550, 3551, 3555, 3711, 4733, 3952)
- Fax over IP (ITU-T: T4, T30, T38, V17, V21, V27 ter, V29)

## Connectivity

### Physical interfaces

- Premise connections:
  - 1 LAN Ethernet 10/100/1000 BASE-T port(RJ-45)
  - 1 Ethernet 10/100 BASE-T port (RJ-45) for redundancy connection

### Uplink connections:

- 1 WAN Ethernet 10/100/1000 BASE-T (RJ45)

### Audio port connections:

- Line-in/line-out (line-in signal level - 0.5V RMS, Line-out  $R_{load}$  - 600Ohm to 10K Ohm)

### USB connections:

- USB host, type A
- USB OTG, mini type AB

### Phones

- IP phones:
  - 100 SIP phones by default
  - 400 additional SIP phones may be added with feature keys
  - All SIP phones can be connected both from LAN or WAN side or as remote extensions
  - Auto provisioning support for all IP phones from selected manufacturers
  - PnP configuration support for the most of IP phones from selected manufacturers
  - Auto configuration using OpenVPN service for some of selected IP Phones

### Auto Attendants and Virtual extensions

- Auto Attendants:
  - Up to 800 standard and custom Auto Attendants can be registered

### Virtual extensions:

- Up to 800 virtual extensions can be registered\*\*

\*\*The total number of extensions used for IP phones, Auto Attendants and virtual extensions can not exceed 800.

### System Capacity

- Up to 80 simultaneous VoIP calls with external parties
- Unlimited station-to-station calling for IP phones

### Memory Storage

- microSD card

## Network

- STUN/Network Address Translation (NAT) traversal (RFC 3489)
- IPSec VPN with 3DES and AES encryption in tunnel mode (RFCs: 2402, 2406, 2409)
- Automatic Internet Key Exchange (IKE) keying support
- OpenVPN
- PPTP VPN, L2TP VPN
- Firewall security via:
  - Intrusion Detection System (IDS)
  - Network Address Translation (NAT)

- Policy and service-based filtering Stateful inspection firewall
- SIP Intrusion Detection System (SIP IDS)
- DHCP server on the LAN side
- DHCP client on the WAN side
- DNS server with forwarding functionality
- Simple Network Time Protocol (SNTP) server/client for computer clock synchronization
- PPPoE connection to the ISP with PAP/MS CHAP authentication
- IP DIFFSERV for QoS
- SIP tunneling
- Virtual LAN (VLAN/IEEE 802.1Q)
- Mail client to send voice and fax messages as email attachments (.wav and .tif/.pdf respectively) and system notifications
- DNS (DYNDNS) support with third party NAT/router with port forwarding and port translation

## System

### Management

- Multilingual web interface accessible from LAN and WAN (HTTP/HTTPS)
- Password control
- User rights management
- Remote diagnostics and software upgrade
- VoIP Carrier Wizard
- Download/restore configuration
- Legible and editable configuration files
- Auto configuration of IP phones via TFTP and HTTP
- SNMP monitoring and configuration
- Third Party Call Control (3PCC) XML RPC\*
- Reset button with factory reset option
- Extension status watching (with DCC)
- Custom language pack
- System event notification via SMS/email
- Emergency recovery

### Diagnostics/Testing

- System status LED
- Remote testing
- Network diagnostics
- Security diagnostics
- System logs, SIP IDS logs
- Call capture

### Billing and Statistics

- Radius Client (RFCs: 2865, 2866), Call Detail Records (CDR)

## Environmental

### Physical Dimensions

#### Rack-mountable devices:

- Measurements:
  - 8.0" x 4.0" x 1.6" (20.5 x 10.5 x 4.0 cm)
- Weight:
  - 1.26 lbs. (570 g)

### Conditions

- Operating temperature:
  - 41°F - 104°F (5°C - 40°C)
- Storage temperature:
  - 41°F - 140°F (5°C - 60°C)
- Non-condensing humidity:
  - 5% - 90%

### Powering Options

- Input: 85-264VAC, 47-63Hz, AC
- Input from type AB mini-USB,
- Input from 5VDC/2A adapter

### Power Consumption

- 2.7W (idle), 6.5W (max)

Epygi Technologies, Ltd.  
2233 Lee Road, Suite 201  
Winter Park, Florida 32789

Tel: (+1) 972.692.1166  
Web: www.epygi.com  
E-mail: sales@epygi.com