

Component-based approach

The pbxnsip product makes it possible to choose best-ofclass components to set up the corporate communication infrastructure. You may choose the hardware platform of your choice (Windows-based or Linux-based), you may choose your server hardware, your PSTN termination, your handsets and you may integrate new devices like WiFi cell phones into your system.

Localization and Configuration

Settings The PBX comes with selected pre-Settings recorded languages (e.g. US-English, German, French, Spanish, and Russian); other languages can be added easily. The auto attendant is able to prompt the user to select a language, which makes it possible to use the PBX with dual language requirements. Texts for emails can be customized using language definition files. The built-in web server supports multiple languages. All localization settings can be defined on domain and extension level.

In order to support easy and safe installation, the PBX includes a tftp server that generates configuration files for selected user-agents on the fly (e.g. Cisco phones models 79xx version 8.x, Polycom 2.x versions, snom 7.x versions). Other user agents can easily be added by simple configuration file templates.

Security and Monitoring

The PBX protects the caller's privacy by using the latest IETF standards (TLS, SRTP, and SDES). Operators have access to calls by barge-in, teach-mode or listening-in. Calls can be recorded to the file system or sent to a SIPbased monitoring port. The PBX maintains the security context, so that these features are also available when SRTP is being used.

Certificate ration uration Certificate System Statu update

ettings Accounts Trunks Dial Plans Status Settinas

Managing Head Office (localhost)

as well as the numbers of your extensions.

This pag

Setting

Gener

SIP

Jse St

Gene

S

IP Setu

IP C

produc

LAN

Addr

IP A

Ne

TF

are mapped to star codes. Accounts are anything that you can dial on your PBX. Accounts include Extensions, Auto Attendants, Conference Rooms. These numbers may be service numbers of the PBX

Domain Settings are necessary to customize the behavior

of the PBX in this domain. Here you can define how features

Trunks are used to connect your PBX to the outside world. Trunks can be PSTN gateways in your network or they can be ITSP accounts that you signed up for. Trunks are also important for matching incoming calls

Dial Plans tell the PBX how to reach an outside number. Usually you will use a trunk to terminate outgoing calls. Each extension may have its own dial plan. With this technology, you can allow or restrict extensions from making calls to specific numbers.

The Status shows you what is going on in the domain. You can see which calls are active and which calls took part in the domain. If you are logged in with system administration permissions, you may also access the system log from there.

Paging and Intercom

The PBX supports these popular functions by using standard SIP and multicast RTP. This makes it possible to implement small paging groups up to large corporate announcement systems. Music on hold can be sourced from files and RTP streaming.

PBX Functions

The PBX supports hunt groups and waiting queues. All services can be run in day/night mode. If necessary, simple IVR dialogs can be set up and external databases can be queried for routing purposes. A built-in conference mixer is able to host unmanaged conferences. In addition to the build-in mailbox system, external, SIP-based voice mail systems (for example, Microsoft® Exchange 2007) can be integrated.

Copyright © 2008 pbxnsip Inc. All rights reserved. Trademarks or registered trademarks mentioned in this document are the property of their respective manufacturers or owners unless stated otherwise. Product specifications contained in this document are subject to change without notice.



NAT and Mini-SBC

The service runs on hosts with multiple IP addresses. For example, several private and public IP addresses can be mixed. A built-in mini-session border controller makes sure that devices behind NAT can be registered to the PBX. This makes it possible to run the service for extensions in the LAN and at home offices.

The PBX also supports the allocation of public IP addresses using STUN. This is necessary for some ITSP in order to present them with a routable address.

Cell Phone Support

The PBX supports multiple registrations per extensions. The user may decide to ring the cell phone after a certain time when the extension does not pick up. When receiving a voicemail message, the PBX may call the cell phone and read the message out.

For international calls, PBX users can call from their cell phones into the PBX to place international calls using the PBX's dial plan and rates. This significantly reduces the communication costs for international oriented companies.

10 good reasons for the pbxnsip PBX

- **1.** It truly supports SIP.
- 2. It meets your security needs.
- 3. It runs on Windows and Linux.
- 4. It supports plug and play.
- 5. It supports trunks to your ITSP.
- 6. It talks to your PSTN gateway.
- 7. It addresses NATs and firewalls.
- 8. It is callable from the Internet.
- **9.** It is affordable.
- 10. It makes VoIP simple!

Management

10101001010101

001010101010101010

101011101 1010

1011101010101

Management costs make up a large portion of the total cost of ownership when running services like a IP-PBX. The pbxnsip significantly compared to other products. Using only the file system makes backup and redundancy easy. Most of the administration can be done from the web interface of the PBX.

10101010101010101010100 01011010101 0101010101010 01010

01010101010101010101 010101011107

1010101010101010101010101

A built-in SNMP agent makes it possible to integrate the PBX into the overall corporate monitoring system.

Presence and IM

The PBX supports sharing presence information and instant messaging (IM). This makes it possible to operate these services independently from public vendors. This has the advantage that users do not get distressed by public IM traffic during work hours. A built-in SNMP agent makes it possible to integrate the PBX into the overall corporate monitoring system.

Busy Lamp and CO-Lines

The PBX supports these popular functions by using standard SIP and multicast RTP. This makes it possible to implement small paging groups up to large corporate announcement systems. Music on hold can be sourced from files and RTP streaming. Selected devices also allow music on hold input from the audio input jack.

Licensing

Version 2.0 offers a large number of license options. License bundles for typical setups can be obtained from qualified resellers. Additional options can be added to the bundles.

Ask for upgrade licenses from previous versions to 2.0

Contact

For more information on the product, go to http://www. pbxnsip.com. For technical documentation, go to http://wiki. pbxnsip.com. For other information, send email to info@pbxnsip.com or call 978-746-2777.



Distributed by ABP Technology 1850 Crown Drive, Suite 1112 Dallas, TX 75234 972-831-1600 www.abptech.com