

# WPU-7700



**Fully Compliant with Industry Standards 802.11 and SIP**

Flexible solution with no additional proprietary back-end proxy



#### **Fast-secure roaming**

Offering the best voice quality through multiple secured WLAN profiles

#### **A variety of additional features**

SMS, phone book, call history, mute, transfer, pick up, forward, hold, block, alarm, simple html browser

#### **Robust security**

A variety of wireless LAN security functions to use anywhere in enterprise and residence

#### **Modular software**

Offering stable customization with stability for vendor specified features

#### **About UniData**

UniData Communication Systems, Inc., with headquarter in Seoul, Korea, is one of the world's foremost provider of Wi-Fi phone products. With expertise in diverse platform optimization and commercially proven solution, the company offers the most reliable Wi-Fi phone customization to enterprise solution and tier service provider platform. For more information on UniData and its Wi-Fi solutions, visit the company's website at [www.udcsystems.com](http://www.udcsystems.com)

#### **ABP Technology**

1850 Crown Drive, Suite 1112 . Dallas, TX 75234 . USA  
Tel: 972-831-1600 . Fax: 972-831-1416  
E-mail: [sales@abptech.com](mailto:sales@abptech.com)  
[www.abptech.com](http://www.abptech.com)

## Software Specification

Features	Spec
Wireless LAN	WMM for QoS Enhanced power consumption for longer battery life
Wireless Security	WEP(64/128 bits) / WPA-PSK / 802.1x EAP-MD5, EAP-TTLS, PEAP, EAP-TLS* WPA/WPA2-personal and enterprise
Dynamic Network Binding	Pre-configured 5 network profiles for auto connection DHCP / Static IP / DiffServ (ToS) Tagging NAT Traversal: STUN, L2/ L3 fast roaming
Voice over IP	RFC3261 SIP G.711, G.729AB, Jitter buffer In-band DTMF / Out-of-band DTMF(INFO, RFC2833) SIP Message SIP/SIMPLE Presence and Chatting
Call Features	Mute / Hold / Transfer (attended/unattended/consultant) Waiting / Forwarding (busy / no answer / unconditional) Caller ID display / Call ID blocking 3-way conference (dependant on SIP proxy)
Phone Features	64 polyphonic MIDI ring / Vibrate * Call history (Inbound / Outbound / Missed / Memo, 100 records) Phone book (500 records) / Speed dial (99 records) Distinctive ringing (by individuals and / or groups) Phone book search during call
Applications	Simple HTML browser (Google mobile, customizable multimedia service) Alarm / Morning Call / D-Day / Calculator / World Time
Management	Auto/Manual upgrade(HTTP/HTTPS) / Auto provisioning (HTTP/HTTPS) SNTP Time synchronization / Syslog remote logging* Web server for user phone book configuration

## Hardware Specification

Item		Specification
Physical Dimension	Main Unit	Dimensions(H x W x D): 5.4 x 1.9 x 0.9 in. (13.8 x 4.8 x 2.2 cm)
	Weight	Weight: 3.7oz (106g)
	Display	128 X 160 pixel , 65K TFT-LCD
	Backlight	LCD: White LED, Button: Blue LED
Hardware	Button	Number key (0-9,*,#), Send, CLR, End, Navigation key (up, down, left, right, enter), 4 soft keys
	Audio	MIC, Receiver, Speaker
	Other	Vibrate *, Charger terminal
	Standards	IEEE 802.11b/g
	Protocol	CSMA/CA
Wireless Radio	Modulation	802.11b :DBPSK, DQPSK, CCK 802.11g : 16-QAM, 64-QAM
	Frequency Band	2400 ~ 2483 MHz (13CH)
	Rx Sensitivity	-88dBm@11Mbps
	Output Power	15dBm/22MHz for 11Mbps 14dBm/22MHz for 54Mbps
Battery	Li-ion Polymer Battery	Capacity - 3.7V 1300mAh
		Talk time - About 5hours
		Standby Time - About 70hours
Environmental Conditions	Operating temp / Humid	32 to 122 °F (0 to 50 °C), Relative humidity: 10~85% RH

\* Optional \*\* It depends on WLAN device and its network structure.  
Trademarks and service marks are the property of respective holders.