



Distributed by: ABP Technology Partners
 1203 Crestside Drive, Suite 300, Coppell, TX 75019
 972.831.0280 www.abptech.com

Manufacturers Features
 Product Comparison

Red Hawk/CDT
 BL-80xx PowerSense™

PowerDsine
 PD-60XX



Form Factor:		
<i>Modular Chassis</i>	Yes	No
Safety Protection:		
<i>High voltage over protection fuse</i>	Yes	No
<i>Low voltage reset able fuse</i>	Yes	Yes
Detection Protocols Supported:		
<i>Legacy 24 Volt PowerDsine Protocol</i>	Yes	Yes
<i>48 Volt IEEE802.3af</i>	Yes	Yes
<i>Cisco Detect Protocol</i>	Yes	No
Product Customization For:		
<i>Detection/Voltage</i>	Yes	No
Classification	No	Yes
	Not required, full 15.6W per port	Does not provide full power per port
LED Diagnostics	4 per port	1 per port
Voltage Isolation	2000V between ports	none
Hot swappable Modules	Yes	No
Rack Mountable	Yes - 2U	Yes - 1U
SNMP	No - Q/1 (2003)	Yes

For more Information about PowerSense™ visit www.abptech.com or call:

ABP Technology Partners
 1203 Crestside Drive, Suite 300, Coppell, TX 75019
 Phone:972.831.0280 Fax:972.831.1416

Copyright © 2002 Red Hawk/CDT. PowerSense™ is a trademark of Red Hawk/CDT. While Red Hawk/CDT believes the foregoing information is accurate, Red Hawk/CDT has made no investigation and does not make any representation or warranty as to its accuracy or completeness and reserves the right to change specifications at any time without notice. Red Hawk/CDT will not be liable for any errors or omissions in the foregoing, including any damages (whether incidental, consequential or actual) resulting from the publication, distribution or use of, or reliance on, the foregoing information. All corporate identities mentioned in this document are trademarked with their respective corporations.