

DrayTek's line of switches can now be combined with IPTECHVIEW™ to offer a true secure cloud-managed switch solution. When the switch is provisioned for IPTECHVIEW, its GUI can be accessed remotely without having to install cloud access hardware clients onsite or set port forward rules on routers or firewalls.

The IPTECHVIEW remote monitoring and management solution constantly monitor the health of the device, triggering alerts when custom-defined thresholds (memory, CPU, power used, etc.) are breached. This unique, agentless solution brings full LAN monitoring and management capability to the Cloud!



Dray Tek

Cloud Monitored and Managed Gigabit PoE Switches



P1085-IPT

- · Max port speed: 1G
- · Ports: 8 GbE
- PoE Ports: 8
- PoE Power Budget: 140 Watts
- · Switching Capacity: 16 Gbps
- Forwarding Rate: 11.9 Mpps
- · MAC Address Table: 8k
- VLAN: Tag-based, MAC-based, Voice, Surveillance
- Traffic Control: Storm Control, DoS Defense
- · Security: IPSG, ACL
- Spanning Tree Protocol: STP, RSTP
- Link Aggregration Group: 8 (up to 8 members each group)
- · Multicast: IGMP Snooping
- SNMP: v1, v2c, v3
- Locally Managed
- Cloud Managed
- · Cloud-controlled PoE ports
- Cloud monitored and maged.
 Full GUI access from
 IPTECHVIEW™ platform



P1280-IPT

- · Max port speed: 1G
- Ports: 24 GbE + 4 SFP/GbE Combo
- PoE Ports: 24
- PoE Power Budget: 340 Watts
- · Switching Capacity: 56 Gbps
- · Forwarding Rate: 41.7 Mpps
- MAC Address Table: 8k
- VLAN: Tag-based, MAC-based, Voice, Surveillance
- Traffic Control: Storm Control, DoS Defense
- · Security: IPSG, ACL
- Spanning Tree Protocol: STP, RSTP
- Link Aggregration Group: 8 (up to 8 members each group)
- · Multicast: IGMP Snooping
- SNMP: v1, v2c, v3
- Locally Managed
- · Cloud Managed
- Cloud-controlled PoE ports
- Cloud monitored and managed.
 Full GUI access from
 IPTECHVIEW™ platform



P2280x-IPT

- · Max port speed: 10G
- Ports: 48 GbE + 6 SFP/GbE Combo
- PoE Ports: 48
- PoE Power Budget: 400 Watts
- Switching Capacity: 216 Gbps
- Forwarding Rate: 160.7 Mpps
- MAC Address Table: 32k
- VLAN: Tag-based, MAC-based, Voice, Surveillance, GVRP, QinQ
- Traffic Control: Storm Control, DoS Defense
- Security: IPSG, ACL, 802.1x, DAI, DCHP Snooping
- Spanning Tree Protocol: STP, RSTP, MSTP
- Link Aggregration Group: 8
 (up to 8 members each group)
- Multicast: IGMP Snooping, MLD Snooping
- SNMP: v1, v2c, v3
- · Locally Managed
- · Cloud Managed
- · Cloud-controlled PoE ports
- Cloud monitored and managed.
 Full GUI access from
 IPTECHVIEW™ platform

